

Package: ccpsyc (via r-universe)

November 5, 2024

Type Package

Title Methods for Cross-Cultural Psychology

Version 0.2.7

Description With the development of new cross-cultural methods this package is intended to combine multiple functions automating and simplifying functions providing a unified analysis approach for commonly employed methods.

License GPL-3

Depends R (>= 4.0.0)

Imports magrittr, dplyr, lavaan, readr, MCMCpack, psych, ufs, tibble, rlang, RcppAlgos, tidyr

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

LazyData true

RoxygenNote 7.2.0

Roxygen list(markdown = TRUE)

Config/pak/sysreqs libfontconfig1-dev libfreetype6-dev libgmp3-dev
make libicu-dev libpng-dev libxml2-dev libx11-dev

Repository <https://jo-karl.r-universe.dev>

RemoteUrl <https://github.com/jo-karl/ccpsyc>

RemoteRef HEAD

RemoteSha e4002f3961e0a47eaf0bb54d43c56f0d2fbe29bb

Contents

boot_inv_eff	2
clearing_fa	3
dMACS	4
equival	4

example	5
format_boot_inv_eff	6
gamma_hat_scaled	7
invariance_eff	7
lavTestScore.clean	8
mg_rel_table	8
MNCI	9
multi_group_eff	9
pancultural	10
prost	11
release_bonferroni	11
splitgroup	12

Index	13
--------------	-----------

boot_inv_eff	<i>Bootstrapped pairwise differences in psychometric function of groups.</i>
--------------	--

Description

Bootstrapped pairwise differences in psychometric function of groups.

Usage

```
boot_inv_eff(
  n,
  n_sample,
  df,
  items,
  group,
  eff_sizes = c("SDI2", "UDI2", "WSDI", "WUDI", "dmacs"),
  seed = 2711
)
```

Arguments

n	Number of bootstraps
n_sample	Number of participants to sample
df	Data to resample
items	Items to resample for the model as vector of strings
group	String variable indicating grouping variable
eff_sizes	Effect sizes to be returned
seed	Seed for replicability

Value

Returns a dataframe with the bootstrapped effect sizes based on the `invariance_eff` function in this package for two country comparisons.

Examples

```
two_country <- dplyr::filter(example, country %in% c("NZ" , "BRA"))
boot_inv_eff(n = 10,
             n_sample = 200, df = two_country, group = "country",
             items = paste0("voice",1:3, "m"))
```

clearing_fa

*Function to quickly organize and clear psych factor loadings***Description**

Function to quickly organize and clear psych factor loadings

Usage

```
clearing_fa(
  psych_fa,
  cutoff = 0.4,
  dbl_dist = 0.2,
  key_file = NULL,
  cleaned = TRUE
)
```

Arguments

<code>psych_fa</code>	Output from the psych package, can be either fa or principal with at least two dimensions
<code>cutoff</code>	Desired cutoff below which loadings are omitted defaults to .40
<code>dbl_dist</code>	Desired distance between highest and second highest loading for an item to remove double loadings, defaults to .20
<code>key_file</code>	Optional: Either a .csv or .xlsx file with at least two columns: 1 labeled item containing the item labels as in the data frame, 2 a column labeled wording containing the item wording.
<code>cleaned</code>	If true (default), only the cleaned solution with a message for descriptive stats are returned. If false the function returns a list of data frames one cleaned and one showing all in-between steps

Value

`clean` This column contains the assignment after removing NAs and double loadings

`dir` This column contains the direction (positive or negative) of the highest loading.

Examples

```
library(psych)
fa_solution <- fa(example[c(paste0("help", 1:6, "m"), c(paste0("voice", 1:5, "m")))], nfactors = 2)
clearing_fa(fa_solution)
```

dMACS	<i>Computes dMACS</i>
-------	-----------------------

Description

Computes dMACS

Usage

```
dMACS(fit.cfa, group1, group2)
```

Arguments

<code>fit.cfa</code>	Lavaan output object with two groups and a single factor.
<code>group1</code>	String for first group in the grouping factor
<code>group2</code>	String for second group in the grouping factor

Value

Returns dMACS for each item.

Examples

```
dMACS
```

equival	<i>One-step equivalence testing The function allows for a simple one step test of configural, metric, and scalar equivalence between multiple groups.</i>
---------	---

Description

One-step equivalence testing The function allows for a simple one step test of configural, metric, and scalar equivalence between multiple groups.

Usage

```
equival(x, dat, group, standart_lv = TRUE, orthog = TRUE, estim = "MLM")
```

Arguments

<code>x</code>	CFA model identical to models provided to lavaan.
<code>dat</code>	A data frame or tibble containing the raw data for the specified model.
<code>group</code>	A character string that indicates the column of <code>dat</code> that contains the grouping variable. e.g "country"
<code>standart_lv</code>	A boolean that indicates whether the latent variables should be standardised.
<code>orthog</code>	A boolean that indicates whether the latent variables should be orthogonal.
<code>estim</code>	A string indicating the estimator to be used MLM for complete data and MLR for incomplete data. Defaults to MLM

Value

Returns a data frame with the fit indices for each model and delta values comparing the different levels of equivalence. **For a step by step interpretation see.**

Examples

```
model <- "voice =~ voice1m + voice2m + voice3m
         help  =~ help1m  + help2m  + help3m"
equival(x = model, dat = example, group = "country")
```

example

Help and Voice Behavior in different countries

Description

Help and Voice Behavior in different countries

Usage

```
example
```

Format

A data frame with 5201 rows and 13 variables:

country Country of sample
help1m First Help Item
help2m Second Help Item
help3m Third Help Item
help4m Fourth Help Item
help5m Fifth Help Item
help6m Sixth Help Item

help7m Seventh Help Item
voice1m First Voice Item
voice2m Second Voice Item
voice3m Third Voice Item
voice4m Fourth Voice Item
voice5m Fifth Voice Item
...

Source

<https://www.frontiersin.org/articles/10.3389/fpsyg.2019.01507/full>

format_boot_inv_eff *Improving boot effectsize output*

Description

Improving boot effectsize output

Usage

```
format_boot_inv_eff(x)
```

Arguments

x The output of a bootstrapped invariance effect call

Value

A formatted tibble with all effect sizes reported by boot_inv_eff from this package and significant determined by 95% CIs either crossing 0 or .30

Examples

```
two_country <- dplyr::filter(example, country %in% c("NZ" , "BRA"))
boot_inv_eff_result <- boot_inv_eff(n = 10,
                                   n_sample = 200, df = two_country, group = "country",
                                   items = paste0("voice",1:3, "m"))
format_boot_inv_eff(boot_inv_eff_result)
```

gamma_hat_scaled	<i>Gamma Hat from MLM fitted lavaan object</i>
------------------	--

Description

Gamma Hat from MLM fitted lavaan object

Usage

```
gamma_hat_scaled(object)
```

Arguments

object	A lavaan output object that was fitted with a MLM estimator
--------	---

invariance_eff	<i>Invariance Effect Sizes</i>
----------------	--------------------------------

Description

Invariance Effect Sizes

Usage

```
invariance_eff(
  df,
  items,
  group,
  nodewidth = 0.01,
  intercept_fix = 1,
  lowerLV = -10,
  upperLV = 10,
  ...
)
```

Arguments

df	Multi-group dataframe
items	vector of items for the target construct
group	string defining grouping variable
nodewidth	Steps tested
intercept_fix	Which item should have a fixed intercept defaults to the first item
lowerLV	Lower range of latent variable tested
upperLV	Upper range of latent variable tested
...	Passes on to lavaan CFA functions

Value

Returns a dataframe with a row for each item comprising the uni-factorial solution and one column for each invariance effect size. A detailed interpretation of each effect size is provided in [Gunn et al. \(2019\)](#).

lavTestScore.clean	<i>Get more comprehensible output from lavTestScore</i>
--------------------	---

Description

Get more comprehensible output from lavTestScore

Usage

```
lavTestScore.clean(lavaan.fit, ndigit = 3, ...)
```

Arguments

lavaan.fit	Model fitted with lavaan
ndigit	Defines the rounding
...	Arguments passed to lavTestScore

Value

Returns a dataframe which contains one row for each constrained parameter in the model together with a chi-square test indicating whether the parameter significantly differs between groups. This is a cleaned version identical to [lavTestScore](#).

Author(s)

Maksim Rudnev

mg_rel_table	<i>Multi-group reliability table</i>
--------------	--------------------------------------

Description

Multi-group reliability table

Usage

```
mg_rel_table(df_s, measure_list, group, digitn = 3, seed = 2711)
```


Arguments

<code>df_s</code>	The full dataframe with all groups and items.
<code>measure_list</code>	A named list of vectors containing the item names. The format should be <code>list(measure_name1 = c('Item1', 'Item2', 'Item3'), measure_name2 = c('Item1', 'Item2', 'Item3'))</code>
<code>group</code>	Grouping variable in the dataset as string for example "country"
<code>digitn</code>	Controls the amount of digits shown in the output
<code>seed</code>	Seed for the bootstrapped confidence intervals

Value

Returns a formatted dataframe with the reliability of all constructs by group

MNCI	<i>Non-Centrality Index</i>
------	-----------------------------

Description

Non-Centrality Index

Usage

```
MNCI(object)
```

Arguments

<code>object</code>	A lavaan object that was fitted with a MLM estimator/
---------------------	---

<code>multi_group_eff</code>	<i>Pairwise Effect sizes of similarities and difference in the psychometric structure between multiple groups</i>
------------------------------	---

Description

Pairwise Effect sizes of similarities and difference in the psychometric structure between multiple groups

Usage

```
multi_group_eff(
  df,
  group,
  items,
  eff_sizes = c("SDI2", "UDI2", "WSDI", "WUDI", "dmacs")
)
```

Arguments

df	Multi-Group data frame
group	String variable indicating the grouping variable
items	Vector of strings indicating items for the uni-factorial construct
eff_sizes	Effect sizes to be returned

Value

The function returns a list of dataframes with the first reporting the averaged results per item and the second reporting the pairwise comparisons.

Examples

```
example_s <- dplyr::filter(example, country %in% c("NZ", "BRA"))
multi_group_eff(df = example, group = "country", items = paste0("voice",1:3, "m"))
```

pancultural

Creating a Pan-Cultural Loading Matrix

Description

Creating a Pan-Cultural Loading Matrix

Usage

```
pancultural(df, group, nfactors)
```

Arguments

df	A data frame contains the variables for the exploratory factor analysis and the grouping variable.
group	The name of the column tht cointains the grouping supplied as a string.
nfactors	The number of factors expected.

Value

returns a Pan-Cultural loading matrix.

Examples

```
pancultural(example, "country", 5)
```

prost	<i>Procrustes rotation function, returning Tucker's Phi</i>
-------	---

Description

Procrustes rotation function, returning Tucker's Phi

Usage

```
prost(loading, norm, rotated = FALSE, digits = 2)
```

Arguments

loading	A correlation matrix to be rotated towards a target
norm	A correlation matrix that is the goal of the rotation
rotated	A TRUE/FALSE operator indicating if the rotated matrix should be returned in addition to Tucker's Phi
digits	The number of digits to be displayed in the output, defaults to 2

Value

Returns Tuckers Phi evaluating the congruence of the loading matrix to the normative matrix

release_bonferroni	<i>Examining chisquare improvement if paths are unconstrained. The function returns the paths to be unconstrained based on chisquare change. Adjusted P-values are calculated based on iterative Bonferroni corrections.</i>
--------------------	--

Description

Examining chisquare improvement if paths are unconstrained. The function returns the paths to be unconstrained based on chisquare change. Adjusted P-values are calculated based on iterative Bonferroni corrections.

Usage

```
release_bonferroni(lavaan.fit, ndigit = 3, exp_p = 0.05, ...)
```

Arguments

lavaan.fit	Model fitted with lavaan
ndigit	Number of digits to round chi and p to
exp_p	Expected p-value
...	Arguments passed to lavTestScore

Value

Returns a dataframe representing a Bonferroni corrected version of [lavTestScore.clean](#).

Author(s)

Maksim Rudnev

splitgroup	<i>Split by groups</i>
------------	------------------------

Description

Split by groups

Usage

```
splitgroup(df, group, named = FALSE, name.list = NA)
```

Arguments

df	Dataframe
group	Variable from the dataset that defines the groups
named	TRUE/FALSE argument wheter the resulting list should be named
name.list	Supply a list of names same length as number of groups

Value

Returns a list of dataframes with only the selected groups

Index

* datasets

example, 5

boot_inv_eff, 2

clearing_fa, 3

dMACS, 4

equival, 4

example, 5

format_boot_inv_eff, 6

gamma_hat_scaled, 7

invariance_eff, 7

lavTestScore, 8

lavTestScore.clean, 8, 12

mg_rel_table, 8

MNCI, 9

multi_group_eff, 9

pancultural, 10

prost, 11

release_bonferroni, 11

splitgroup, 12